



Brew & Go Hot Brewer

BREWER ELEMENTS:

1. Stainless Steel Brewer (A)
2. Clear Top (B) with Attached Silver Lid & Red Gasket
3. Removable Filter (C) With Wire Frame Attached
4. Vacuum Pump (D)
5. Stopper (With Two Washers and 1 Red Centering Ring Attached) (E)
6. Silicone Funnel (F) (optional)
7. Two Travel Bags (G)
8. Travel Lid (H)



BEFORE USE:

- Wash all elements in hot soapy water before use
- NOT dishwasher or microwave safe
- Use Caution! Beverage is very hot!
- We encourage preparing coffee in a sink for safety reasons

Questions?

Contact us at Info@Noaircoffee.com

Step 1: Add 3-6 TBS (scoops) (15-30 grams) coffee into basket of the removable filter (C). Then connect the filter's top to filter basket & lower into the brewing vessel by the filter's handle (A). Gently squeeze handle as it descends,



Step 2: FOR SAFETY REASONS, WE SUGGEST STEP 2-6 BEING DONE IN A SINK.

Pour 600 ML or 20 oz hot/boiling water into the vessel. **ONLY fill to top of brewer's Threads. Do not overfill.** (You will be able to see the hot liquid as it tops the brewer's threads). Then, remove silver cap from clear top (B) and set straight down onto brewer, so it sits nestled into brewer (**Do not engage threads-** as the vacuum pressure will keep top attached).



Step 3: Insert Stopper (E) (with two white washers and one red centering ring attached) into the neck of the clear top (B). Then set vacuum pump (D) onto stopper. Carefully push Pump and Stopper down so stopper sits firmly into the neck.

***USE CAUTION COFFEE IS HOT!**



Step 4: CAREFULLY draw a vacuum by drawing upwards on the pump 6-8 times (While keeping downward force on pump). Foam will appear - stop pumping before foam reaches the stopper.

***Steps 2-6 are best done while Brewer is in a sink for safety reasons**

Step 5: Let brew for 60 seconds. Gently swirl, then re-draw a vacuum (draw upwards 4-6 times) and let brew for another 30 seconds



Step 6: Remove stopper by moving its top knob right or left until you hear (hiss) release of vacuum. Then carefully lift to remove the clear top (B), and remove the filter (C) by its handle, and set aside.

Attach travel lid by screwing it into the brewer's threads, Then GO and enjoy!

Thank you for your support!
Reach out to us at Info@Noaircoffee.com for any questions or concerns.
Visit our website for more information, recipes, videos and other great coffee brewers!

Noaircoffee.com

Find Recipes, Manuals and troubleshooting information at Noaircoffee.com

Knob. Push right or left to release pressure

